DRV30-13RL

DDR3-1333, PC3L-10600, Registered, ECC, 1.35V, 240-pin DIMMs

Products in Family

DRV30-13RL/8GB (1 x 8GB 2Rx4 DIMM)
DRV30-13RL/16GB (1 x 16GB 2Rx4 DIMM)

Features	Description
240-pin JEDEC-compliant DIMMs 133.35 mm wide by 30 mm high (1.181” x 5.25”) Data Transfer Rate: 10.6 Gigabytes/sec Operating Voltage: 1.35 V ±0.075 (1.5 V tolerant) Fully RoHS Compliant Thermal Sensor Heat Spreader	Each DRV30-13RL upgrade consists of a single DDR3-1333 Registered DIMM that conforms to JEDEC’s DDR3, PC3L-10600 standard. One 2K-bit EEPROM is used for Serial Presence Detect and a combination register/PLL with Address and Command Parity is also used. A thermal sensor accurately monitors the DIMM module and can prevent exceeding the maximum operating temperature of 95C.

Dataram Product	Lenovo Product	Product Description:
DRV30-13RL/8GB	-------	8GB 2Rx4 PC3L-10600R-9
DRV30-13RL/16GB	-------	16GB 2Rx4 PC3L-10600R-9

Notes

Tolerances on all dimensions except where otherwise indicated are ±.13 (.005).

All dimensions are expressed in millimeters [inches]



Copyright © 2019 Dataram Memory | U.S.A. Headquarters +1 609-799-0071 | Offices in Europe and Asia | www.dataram.com

The information contained in this document has been carefully checked and is believed to be reliable and accurate. However, Dataram assumes no responsibility for errors.